

Description

xFORM D is a multifunctional product that delivers viscosity, hole cleaning and fluid loss control. xFORM D is a simple to use powder product that will help improve drilling efficiency by improving hole cleaning and fluid loss control.

Application

While xFORM D is highly dispersible and therefore well suited to be used where minimal agitation exists, where possible, it should be added via a hopper and allowed the blend in prior to use.

Typical Physical Properties

Appearance:	White to off white powder
Solubility in water:	Soluble

Environmental Information

xFORM D is not classified as hazardous to health or the environment by the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), or under the Globally Harmonized System of Classification and Labelling (GHS).

Biodegradability & Bio Accumulation

Cellulosic compounds, including cellulose ethers such as xFORM D™ generally have a low biodegradation rate and are not believed to bio accumulate

Toxicity

Oral LD50:	>20,000 mg/kg (rat)
Dermal LD50	>2,000 mg/kg (rabbit)

Prepared by AMC Research & Development Laboratory. For further information, please contact your local AMC sales representative.

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.

ASIA PACIFIC

Perth, Australia (Head Office)
+61 8 9445 4000
amc@imdexlimited.com

Indonesia
+61 (0) 21 759 11244

AFRICA

South Africa
+27 (11) 908 5595

EUROPE

Norway
+47 72 87 01 01

Germany
+49 4402 9650-0

United Kingdom
+44 (0) 1273 483 700

SOUTH AMERICA

Argentina
+54 9 261 211 3676

Brazil
+55 (47) 3404 5920

Chile
+56 (2) 2589 9300

Peru / Ecuador
+51 (1) 322 8850

NORTH AMERICA

USA / Canada
+801-364-0233

Mexico
+52 (871) 169 2095