

AMC GROUT 20™

Cement & Grouting Additives



Description

GROUT 20™ is an abandonment and grouting material designed to be mixed with fresh water to form a semi rigid plug. This semi rigid plug can be used for plugging drill holes or grouting water wells and monitoring wells.

Application

GROUT 20™ is designed to be applied as a 20% solids mix. The mixture is pumpable using most common pumping equipment.

Once the 20% mixture is made it can be immediately pumped down hole through a tremie line. To ensure optimal displacement the grout should be pumped through the tremie line from the bottom to surface.

GROUT 20™ is sensitive to water quality. It may not be suitable for use where total hardness exceeds 500mg/L and/or where chlorides exceed 1,500mg/L. Pilot testing using site make up water is advisable prior to use.

Recommended Treatment

To mix a 20% solids slurry 250kg of AMC GROUT 20™ should be mixed into 1000L of fresh water. Alternatively, a 50lb bag of GROUT 20™ should be mixed per 24 gal of fresh water.

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest representative for optimum results.

Typical Physical Properties

Appearance:	Dark red to brown powder
Solubility in water:	Insoluble

ASIA PACIFIC

Perth, Australia (Head Office)
+61 8 9445 4000

Indonesia
+61 (0) 21 759 11244

AFRICA

South Africa
+27 (11) 908 5595

EUROPE

Norway
+47 72 87 01 01

Germany
+49 4402 9650-0

United Kingdom
+44 (0) 1273 483 700

SOUTH AMERICA

Argentina
+54 9 261 211 3676

Brazil
+55 (47) 3404 5920

Chile
+56 (2) 2589 9300

Peru / Ecuador
+51 (1) 322 8850

NORTH AMERICA

USA / Canada
+801-364-0233

Mexico
+52 (871) 680 7146